

FUBA DEK 106

CONVERTITORE SINGLE UNIVERSALE

Cod. Art. 21500057
Cod. Ean. 802442701195-3



CARATTERISTICHE TECNICHE

Uscite	1 uscita per il decoder
Tipo connettore	F-type femmina a tenuta stagna (water proof)
Frequenza ingresso (GHz)	10.70 ~ 11.70 Banda Bassa 11.70 ~ 12.75 Banda Alta
Frequenza uscita (MHz)	950 ~ 1950 Banda Bassa 1100 ~ 2150 Banda Alta
Figura di rumore (dB)	0,7 tipico
Cross polarizzazione (dB)	>23
Guadagno di conversione (dB)	58
Consumo di corrente (mA)	65 tipico
Impedenza d'uscita normale (Ω)	75
Temperatura operativa	-30°C ~ +60°C
Temperatura stoccaggio	-30°C ~ +60°C
Umidità	5% ~ 95% RH
Peso (g)	98,5

TECHNICAL SPECIFICATIONS

Outputs	1 output for the decoder
Output component	F-type female connector (with water proof)
Input frequency (GHz)	10 70 ~ 11 70 Low Band 11 70 ~ 12 75 High Band
Output frequency (MHz)	950 ~ 1950 Low Band 1100 ~ 2150 High Band
Noise figure (dB)	0,7 typ.
Cross polar discrimination (dB)	>23
Conversion gain (dB)	58
Current consumption (mA)	65 typical
Normal output impedance (Ω)	75
Operative temperature	-30°C ~ +60°C
Storage temperature	-30°C ~ +60°C
Humidity	5% ~ 95% RH
Weight (g)	98,5

THE FUTURE TECHNOLOGY

fuba